



## Nfina Technologies™ 602 High-Density, Economical Storage Expansion Unit

### Features:

- 2U Rack-Mount
- 12Gb/s SAS Connectivity
- 12 x 3.5" Hot-Swap Drive Bays
- Up to 144TB per unit
- Easily Daisy-Chained
- Redundant Hot-Swap Power Supplies
- Standard Rails Included
- One 1M SFF-8644 cable Included
- Microsoft® Windows Server® 2012 R2 certified Storage Spaces Server

The Nfina Technologies 602 high density JBOD storage expansion unit provides an easy way to expand capacity in existing systems. The 602 can be easily daisy-chained by using SFF-8644 mini-SAS cables for increased storage capacity. The 602 JBOD is a cost-effective solution for adding storage expansion to Nfina Technologies' Servers, NAS, and SAN products.

Nfina Technologies' 602 JBOD is an important component in maximizing data center efficiency. Our intelligent hardware designs create efficient solutions, thereby substantially lowering energy and IT costs.

Nfina Technologies' products deliver exceptional value, performance, and functionality. Optimized for virtualized computing requirements, our products provide high-density, maximum yield solutions for our customers. Multiple options for high performance computing including I/O, RAID, storage, and memory options, make our products a custom fit for many applications.

At Nfina Technologies, we achieve maximum availability and performance with our server, NAS, SAN, and JBOD products. Our products and components are manufactured to the highest quality standards in the industry for use in the most demanding 24/7 data center applications.

All Nfina Technologies' servers are backed by a five-year limited warranty. Next day and four hour on-site response options are available.

## Specifications

Form Factor	2U Rack, 16.93" x 24.95" x 3.44"
Operating Temperature	10°C to 35°C
I/O Module	One Dual Port SFF-8644 (included) One additional Dual Port SFF-8644 (optional)
Drives	12 x 3.5" Hot-Swap Drive Bays
Connectivity	12Gb/s SAS connectivity
Maximum Storage	Up to 144TB per 602
Input Voltage	100-127 V @ 5.8A, 50/60 Hz 200-240 V @ 2.9A, 50/60 Hz
Power Supply	Redundant Hot-Swap, 460W, Gold-Efficiency
Software Certifications	Microsoft® Windows Server® 2012 R2 certified Storage Spaces Server
Rails	Standard Rails Included (Extended Rails Optional)
Certifications	NRTL Nemko (US/Canada), CE (Europe), Ctick (Australia/NZ), IRAM (Argentina), GS (Germany), FCC (US), CSA (Canada), BSMI (Taiwan), GOST R (Russia), UkrTEST (Ukraine)

Contact: Nfina Technologies, Inc.  
820 S. University Blvd., STE 4E  
Mobile, AL 36609  
Web: [www.nfinausa.com](http://www.nfinausa.com)  
Email: [nfina\\_sales@nfinausa.com](mailto:nfina_sales@nfinausa.com)  
Tel: 251-243-0043  
Fax: 251-316-3884

