

Nfina 602JBOD-A



FEATURES:

- 2U rack-mount enclosure
- 12 x 3.5" hot-swap drive bays
- Up to 144TB storage per unit
- 12Gb/s SAS capable
- LSI® SAS3x36R Expander chip
- 3 x Mini-SAS HD dual ports
- Easily daisy-chained
- Self-discovery and self-configuration
- 2 x hot-swap 80+ Platinum power supplies
- Standard rails included

The Nfina Technologies 602JBOD-A, Economical Solution for Incremental Storage

Designed for maximum storage capacity in a 2U rackmount package, the Nfina Technologies 602JBOD-A is a high-density storage expansion unit that provides an easy way to add incremental storage to existing storage networks. Multiple JBODs can be easily daisy-chained using SFF Mini-SAS cables for high-availability or high-redundancy requirements. This product is ideal for cloud backup, data replication or high-density archive storage applications.

Nfina Technologies' 602JBOD-A is an important component in maximizing IT network performance and efficiency. It is also a cost-effective solution for expanding storage capacity to existing Server, NAS, and SAN products.

At Nfina Technologies we achieve high availability and performance with our servers NAS, SAN and JBOD products. Our designs and components are manufactured to the highest quality standards in the industry for use in the most demanding 24/7 data center applications.

Nfina products deliver exceptional functionality by creating products that are easily customized to fit specific applications. Designed and built for virtualized computing environments, our products provide high-density, maximum yield solutions for our customers. Multiple options for high performance computing, including I/O, RAID, storage, and memory options make our products a custom fit for many applications.

All Nfina Technologies' servers are backed by a five-year limited warranty and include 24x7 tech support with remote diagnostics. Next day and four hour onsite response options are available.

SERVERS

DATA STORAGE

PCs & WORKSTATIONS



NFINA 602JBOD-A

SPECIFICATIONS

Form Factor	2U rack-mount enclosure, 3.5" x 16.9" x 21"
Operating Temperature	0°C to 35°C (32°F to 95°F)
I/O Modules	3 x Mini-SAS HD dual ports (SFF-8644)
Connectivity	12Gb/s SAS connectivity
Drives	12 x 3.5" hot-swap drive bays
Maximum Storage	Up to 144TB per 602JBOD-A
Input Voltage	100-127V @ 6.5A, 50/60 Hz x 2 200-240V @ 3.3A, 50/60 Hz x 2
Power Supply	Redundant hot-swap, 549W, Platinum certified
Rails	Standard rails included
Certifications	UL Recognized, FCC, Hipot tested (USA), CUL Recognized (Canada), CE, RoHS, WEEE Compliant (Europe), TUV Certified (Germany), CCC, RoHS (China), KC (Korea), BSMI (Taiwan)
Warranty	5 years

© 2019 Nfina Technologies, Inc. All rights reserved. Intel®, XEON®, and Intel® Optane™ are registered trademarks of Intel Corporation. LSI® is a trademark of Avago Technologies. Other trademarks and trade names that may be used in this document are owned by their respective companies.

Nfina believes the information in this document is accurate as of its publication date. The information is subject to change without notice. The contents of this document are provided as-is, without any express or implied warranties of any kind.

Rev. 032719

Address: 820 S. University Blvd. Suite 4E, Mobile, AL 36609

Telephone: 251.243-0043

Email: nfina_sales@nfinausa.com

Website: www.nfinausa.com