

Nfina 814i20



FEATURES:

- 2U rack-mount dual-socket server
- Intel® Xeon® Processor E5-2600 v4
- 2 x 10GbE LAN (100/1000/10000), other network options available
- 24 x 2.5" hot-swap drive bays
- 2 x 2.5" hot-swap drive bays
- 12Gb/s SAS capable
- Up to 96TB storage
- LSI® hardware RAID
- Redundant hot-swap power supplies
- Plug-and-play expandability with 600 Series JBOD
- Caching options available
- Microsoft® Windows Server® 2012 R2 certified Storage Spaces Enclosure

The Nfina Technologies 814i20 is a high-value and high-density storage solution ideal for storage and backup applications.

The Nfina Technologies 814i20 delivers a high performance, high-density storage solution, ideally suited for high performance backup and secondary storage applications. The 814i20 can be configured with SSD drives for maximum performance and reliability. Depending on drive type, the 814i20 can provision up to 96TB onboard and storage capacity is easily expanded by adding 600 Series JBOD storage expansion units.

Nfina's NAS storage solutions are ideal for any data center that requires efficient, high speed, and high reliability data storage for big data applications. Data centers for enterprise, military, and municipal government will benefit from Nfina's outstanding value, reliability and performance.

Nfina products deliver exceptional functionality by creating products that are easily customized to fit specific applications. Designed and built for virtualized computing environments, our products provide high-density, maximum yield solutions for our customers. Multiple options for high performance computing, including I/O, RAID, storage, and memory options make our products a custom fit for many applications.

All Nfina Technologies' servers are backed by a five-year limited warranty and include 24x7 tech support with remote diagnostics. Next day and four hour onsite response options are available.

SERVERS

DATA STORAGE

PCs & WORKSTATIONS



NFINA 814i20

SPECIFICATIONS

Form Factor	2U rack-mount, 3.44" x 16.93" x 27.95"
Operating Temperature	10°C to 35°C (50°F to 95°F)
Processor	Intel® Xeon® Processor E5-2600 v4 Family, Up to 22 cores
Socket	Dual R3
Memory	Up to 24 DIMMs, DDR4 ECC 1866/2133/2400/2666 MHz Up to 1.54TB Memory
I/O	Five USB and Two serial ports
Ethernet	2 x 10GbE LAN (100/1000/10000) standard, other options available
PCIe® Slots	One PCIe x4 Gen3 Six PCIe x8 Gen3
Storage	24 x 2.5" hot-swap drive bays (front) 2 x 2.5" hot-swap drive bays (rear)
Maximum Storage	Up to 96TB, depending on drive type
Software RAID	0,1,10, 5
Hardware RAID	LSI® Hardware RAID (optional)
Caching	SSD caching available
Input Voltage	100-127V @ 8.8A, 50/60 Hz 200-240V @ 4.4A, 50/60 Hz
Power Supply	Redundant hot-swap 1100W AC power supplies
Remote Management	Remote Management Module (RMM) included
Trusted Platform Module	Trusted Platform Module (TPM) optional
Software Certifications	Microsoft® Windows Server® 2012 R2 certified Storage Spaces Enclosure
OS Supported	Microsoft® Windows Server® 2012, 2016, Windows® 10 Pro/Enterprise, VMware® ESXi™ 6.0/6.5, Open-E® JovianDSS™ & DSS7, Red Hat® RHEL 5,6,7, SUSE® SLES 11,12, Ubuntu 14,15,16,17, CentoOS™ 6,7, XenServer® 6.5-7.3, more
Certifications	NRTL Nemko (US, Canada), CE (Europe), Ctick (Australia/NZ), GS (Germany), FCC (US), ICES-3(A) (Canada), KCC (Korea), BSMI (Taiwan), EAC (Russia), VCCI-A (Japan)
Warranty	5 years

© 2019 Nfina Technologies, Inc. All rights reserved. Intel®, XEON®, and Intel® Optane™ are registered trademarks of Intel Corporation. LSI® is a trademark of Avago Technologies. Other trademarks and trade names that may be used in this document are owned by their respective companies.

Nfina believes the information in this document is accurate as of its publication date. The information is subject to change without notice. The contents of this document are provided as-is, without any express or implied warranties of any kind.

Rev. 032719

Address: 820 S. University Blvd. Suite 4E, Mobile, AL 36609

Telephone: 251.243-0043

Email: nfina_sales@nfinausa.com

Website: www.nfinausa.com